


Vinkelstång Oliksidig



Dimensioner			Teoretisk massa kg/m	Tvärsnitts- area cm ²	Yta m ² /m	Wx cm ³	Wy cm ³
A mm	B mm	t mm					
30	20	3	1,11	1,42	0,097	0,62	0,29
40	20	3	1,35	1,72	0,097	1,08	0,30
45	30	4	2,25	2,87	0,146	1,91	0,91
50	30	5	2,96	3,78	0,156	2,86	1,11
	40	5	3,37	4,27	0,177	3,02	2,01
60	30	5	3,36	4,29	0,175	4,04	1,12
	40	5	3,76	4,79	0,195	4,25	2,02
65	50	5	4,35	5,54	0,224	5,11	3,18
75	50	6	5,65	7,19	0,244	8,01	3,81
		7	6,51	8,3		9,24	4,39
80	40	6	5,41	6,89	0,234	8,73	2,44
90	60	6	6,82	8,69	0,294	11,70	5,61
		8	8,96	11,4	0,294	15,40	7,31
100	50	6	6,85	8,73	0,292	13,80	3,86
		8	8,99	11,5	0,292	18,00	5,04
		10	11,1	14,1	0,292	22,20	6,17
	65	7	8,77	11,2	0,321	16,60	7,53
120	80	7	10,6	13,5	0,341	19,30	11,40
		8	12,2	15,5	0,391	26,70	13,20
130	65	8	17,8	22,7	0,391	40,40	19,10
		8	11,9	15,1	0,381	31,10	8,72
150	75	12	17,3	22,1	0,381	45,50	12,70
		9	15,4	19,6	0,441	46,70	13,10
	10	18,2	23,2	0,469	53,30	21,00	
	90	12	21,6	27,5	0,469	63,30	24,80
		10	19,0	24,2	0,489	54,20	25,90
100	12	22,5	28,7	0,489	64,40	30,70	
160	80	12	21,6	27,5	0,469	70,00	19,60
180	90	10	20,6	26,2	0,528	75,10	24,00
		12	24,5	31,2	0,528	89,30	25,10
200	100	10	23,0	29,2	0,587	93,20	26,30
		12	27,3	34,8	0,587	111,00	31,30
		14	31,6	40,3	0,587	128,00	36,10